
ECOABRI

Easy and affordable storage in all simplicity



Easy and affordable storage

Designed for easy installation and removal. Saves time for you and your operations. Re-positionable - it can be set up on any type of surface, even without foundations. Its multi-purpose storage and protection (wood, feed, tractors, tools) allows for diverse applications and adaptation to your needs. With ECOABRI, storage is made practical and affordable.



The structure is assembled simply by fitting together the pieces




Solidity is reinforced through locking using self-drilling screws




ECOABRI

Easy and affordable storage in all simplicity

DIMENSIONS	Ecoabri 8,00m	Ecoabri 9,30m
Width	8,00m	9,30m
Minimum length	6,00m	6,00m
Spacing between arches depends		
on the region and altitude	de 0,50 to 1,50m	de 0,50 to 1,50m
Height to roof	3,48m	3,90m






Possible covering

- Coated PVC lorry tarpaulin of pre-stressed colouring (green beige) 500g/m2.
- Very long life.
- SBE farming film 250 microns.
- Ability to fix the cover material using an aluminium clip or ridging.



Green - beige lorry tarpaulin cover


Notes





- Open pinion.
 Coated PVC tarpaulin closed pinion (with venting in the 1/2 moon feature).
- Tarpaulin pinion with rolling door Coated PVC (height 2.80m - length 3.00m).

Rolling door pinion



Open pinion

Plate legs and tie-plugs

Anchors

- Can be installed using cords or film buried by ridging.
- Can also be secured on concrete slabs using plate legs and tie-plugs
- Made of galvanized steel (sendzimir Z275 procedure).

• Structures meet the EN 13031 standard.

In most cases, the construction of these structures simply requires a notification to the local authority.
 However the customer is responsible for finding out about any other possible administrative requirements.

Screw cord

- For use in areas where there is heavy snowfall, Ecoabri can be equipped with special reinforcements. *Contact us.*
- For special applications, the height can be increased up to 50cm. Contact us.

