

GLASS GREENHOUSE DOORS AND AERATION

LATERAL AERATION BY ROLLING:

Cladding.

Plastic: single or double
inflated wall.

Motorised
opening.




CONTINUOUS AERATION IN PINION OR JAMB:

Chassis height: 1m.
Track operated opening system.
Articulation upon request.

AERATION ON VENLO GREENHOUSE



Continuous opening
on the roof.
Quadruple aeration option.



Continuous aeration.



Alternate opening
on the roof.



Alternate opening
with Insect-proof.

Aeration
solutions


Doors
adaptability

➤ To control aeration

on glass greenhouses,
CMF has developed
a set of technical solutions
for opening and for pinion
and jamb aeration.

➤ CMF Group offers

a wide range of doors to meet diverse needs.
Particular attention is given to the quality of
security locks and to model sealing.



Guillotine opening.
Independent
chassis by row.
Height of 1.20m
to 1.50m.
Motorised control.

CMF
CULTURES
BÂTISSEUR DE CLIMATS

DOORS



Sectional doors

- 2 steel surfaces, isolated pre-painted (thickness 40mm).
- Motorised or manual control.
- Width 2.5 to 4m.
- Height: contact us.



Aluminium sliding doors

- Spandrel glass in insulated panel, 30mm thickness.
- Clear glass 4mm thickness.
- Width 1.60m or 3.20m.
- Height: contact us.

Aluminium doors with glazed windows

- Tempered spandrel glass.
 - 4mm tempered glass.
- Width 0.90m or 1.80m.
- Height 2.10m and 2.50m.



Steel doors with fully swinging windows

- Insulated or smooth painted steel container.
- Width 0.90m or 1.80m.
- Height 2.10m or 2.50m.



Dock Equipment

- Lock.
- Leveller.

CMF
CULTURES
BÂTISSEUR DE CLIMATS

Zone Industrielle - B.P.10001
44370 VARADES
T. 33 (0)2 40 98 34 00
F. 33 (0)2 40 98 34 94
mail@cmf-groupe.com

www.cmf-groupe.com